



Material Safety Data Sheet

NOVOCS™ Silicone Solvent

MSDS No. 368

Date of Preparation: October 9, 2012

Revision: 0000

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: NOVOCS™ Silicone Solvent

General Use: Solvent

Manufacturer: Smooth-On Inc., 2000 St. John St., Easton PA 18042

Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic 800-255-3924

International 813-248-0585

Section 2 - Hazards Identification

Hazard Designation:

Europe



Canada



| HMIS | |
|------|---|
| H | 1 |
| F | 3 |
| R | 0 |

F: Highly Flammable N: Dangerous for the environment

Risk phrases pertaining to particular dangers:

R11: Highly flammable.

R50/53: Very toxic to aquatic organisms may cause long term adverse effects in the aquatic environment.

Classified according to Articles 6 & 7 of Directive 1999/45/EC

Section 3 - Composition / Information on Ingredients

| Component | ACGIH TWA | OSHA PEL | Hazard Designation | Weight Percent (%) |
|--|---------------------|---------------------|--------------------|--------------------|
| Hexamethyldisiloxane CAS Number: 107-46-0 EINECS Number: 203-492-7 | None Established | None Established | Xn F | 100 |

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water.

Ingestion: Ingestion is unlikely route of exposure. Do not induce vomiting unless instructed by a physician.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

FlashPoint: 25 °F (-4 °C) .

Flammable Limits: LEL: 1.5 UEL: 14.5 Note: Approximate

Flammability Classification: Flammable Liquid


General Hazard: Material will readily ignite at ambient temperatures. Material can accumulate static charges, which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.

DO NOT Pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; They may explode and cause injury or death. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None

Fire-Fighting Instructions: Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Avoid spraying water directly onto storage containers due to danger of boil over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

**Section 6 - Accidental Release Measures**

Spill /Leak Procedures: Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

Section 7 - Handling and Storage

Handling Precautions: Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. If ventilation is not sufficient, wear proper respiratory equipment. Avoid moisture contamination. Reseal partial containers. Use good general housekeeping procedures.

Storage Requirements: Store in cool dry, well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Protective Clothing/Equipment: Wear chemically protective gloves and aprons to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166.

Section 8 - Exposure Controls / Personal Protection (continued)

Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.



Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics

Section 9 - Physical and Chemical Properties

Product Form: Liquid

Water Solubility: insoluble

Appearance and Odor: Clear, Slight
ethereal odor

Boiling Point: 212°F (100°C)

Specific Gravity: 0.764 g/cm³

Section 10 - Stability and Reactivity

Stability: This product is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Hazardous Decomposition Products: Thermal oxidative decomposition can produce, silicone dioxide, carbon oxides and traces of incompletely burned carbon compounds, formaldehyde.

Section 11- Toxicological Information

Eye Effects: None

Mutagenicity: No Data

Skin Effects: None

Teratogenicity: No Data

Acute Toxicity Effects Data: No data

Section 12 - Ecological InformationEcotoxicity:

Very toxic to aquatic organisms may cause long term adverse effects in the aquatic environment.

Section 13 - Disposal Considerations

Disposal: This material must be disposed of in accordance with local regulations.

Section 14 - Transport Information**DOT****Shipping Name:**

Flammable Liquid N.O.S.
(hexamethyldisiloxane)

Hazard Label:

Flammable Liquid

UN #: 1993

Hazard Class: 3

Packing Group: II

IATA**Shipping Name:**

Flammable Liquid N.O.S.
(hexamethyldisiloxane)

Hazard Label:

Flammable Liquid

UN #: 1993

Hazard Class: 3

Packing Group: II

IMDG**Shipping Name:**

Flammable Liquid N.O.S.
(hexamethyldisiloxane)

Hazard Label:

Flammable Liquid

UN #: 1993

Hazard Class: 3

Packing Group: II

Section 15 - Regulatory Information

United States EPA Regulations:

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.



California Proposition 65: This product does not intentionally contain any chemicals which has been identified by the state of California to cause cancer, birth defects or other reproductive harm.

Canadian Regulations:

WHMIS Identification: CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).



Labeling according to EEC Directive

| Risk Phrases | Symbol(s) Required for EU Label | Safety Phrases |
|--|--|---|
| <p>R11: Highly flammable.</p> <p>R50/53: Very toxic to aquatic organisms may cause long term adverse effects in the aquatic environment.</p> |  <p>F: Highly Flammable</p>  <p>N: Dangerous for the environment</p> | <p>S2: Keep out of reach of children.</p> <p>S9: Keep container in a well ventilated area.</p> <p>S16: Keep away from sources of ignition. No Smoking</p> <p>S29: Do not empty into drains.</p> <p>S33: Take precautionary measures against static discharge.</p> <p>S61: Avoid release to the environment. (See MSDS).</p> <p>S62: If swallowed do not induce vomiting Seek medical advice immediately and show this label.</p> |

16 - Other Information

Disclaimer: The information contained in this MSDS is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Mann Release Technologies Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Directive 1907/2006/EEC (REACH). Hazard symbols and risk phrases are based on maximum listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) or the European Union (EU/EEC) directive 1907/2006/EEC and are considered trade secrets under US Federal Law (29CFR and 40CFR), Canadian Law (Health Canada Legislation), and European Union Directives.